

**DECLARATION OF PERFORMANCE**


No. 402 of 01 October 2014

**KING  
KLINKER**

**Klinkier  
PRZYSUCHA**

1.	Unique Product Type Identification Code: Mass No. 2 (Brown) – Floor tile and clinker step tile																		
2.	Intended Use(s): To tile floors of building structures on the inside and on the outside, including stairs																		
3.	Manufacturer: Klinkier Przysucha S.A. 26 – 400 Przysucha Skrzyńsko ul. Przemysłowa 56																		
4.	Authorised Representative: N/A																		
5.	System(s) for Assessment and Verification of Stability of Performance: System 4																		
6a.	Harmonised Standard: PN-EN 14411:2013 "Ceramic Tiles – Definitions, Classification, Characteristics, Evaluation of Conformity and Marking" Annexe C, Natural																		
6b.	Technical Assessment Body: N/A Notified Body(ies): N/A																		
Declared Performance																			
7.	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 40%;">Essential Characteristics</th> <th style="width: 30%;">Performance</th> <th style="width: 30%;">Harmonised Technical Specification</th> </tr> </thead> <tbody> <tr> <td>Reaction to fire</td> <td>class A1<sub>FL</sub></td> <td rowspan="8" style="text-align: center; vertical-align: middle;">                     PN-EN 14411:2013   <i>Jacek Spólny</i>                      Sworn Translator                      of English                 </td> </tr> <tr> <td>Water absorption</td> <td>below 4%</td> </tr> <tr> <td>Bending strength</td> <td>no less than 800 N</td> </tr> <tr> <td>Slip (anti-slip capacity rating)</td> <td>R 10</td> </tr> <tr> <td>Lifespan for internal use(s)</td> <td>conforming</td> </tr> <tr> <td>Lifespan for external use(s): resistance to freezing and thawing</td> <td>conforming</td> </tr> <tr> <td>Touch</td> <td>NPD</td> </tr> </tbody> </table>	Essential Characteristics	Performance	Harmonised Technical Specification	Reaction to fire	class A1 <sub>FL</sub>	PN-EN 14411:2013  <i>Jacek Spólny</i> Sworn Translator of English	Water absorption	below 4%	Bending strength	no less than 800 N	Slip (anti-slip capacity rating)	R 10	Lifespan for internal use(s)	conforming	Lifespan for external use(s): resistance to freezing and thawing	conforming	Touch	NPD
	Essential Characteristics	Performance	Harmonised Technical Specification																
	Reaction to fire	class A1 <sub>FL</sub>	PN-EN 14411:2013  <i>Jacek Spólny</i> Sworn Translator of English																
	Water absorption	below 4%																	
	Bending strength	no less than 800 N																	
	Slip (anti-slip capacity rating)	R 10																	
	Lifespan for internal use(s)	conforming																	
	Lifespan for external use(s): resistance to freezing and thawing	conforming																	
Touch	NPD																		
8.	Relevant technical documentation or specific technical documentation: N/A																		

Performance of the above specified product conforms to the set of performance characteristics declared. The declaration of performance is issued in accordance with the Regulation (EU) No. 305/2011 under the sole responsibility of the manufacturer specified above.



On behalf of the Manufacturer signed by:  
Michał Wilk  
Head of Quality Control Department

Skrzyńsko 01.10.2014

.....  
Place and date issued

*Jacek Spólny*

.....  
(signature)

**Tłumaczenie jest zgodne z treścią przedstawionego dokumentu**

*I, as a sworn translator of English confirm hereby that the above is a true and accurate translation of the Polish original, IN WITNESS WHEREOF, I have hereunto set my hand and affixed my official seal*